



www.liftex.com
(800) 299-0900

SINGLE LEG ROUNDUP BRIDLE SLINGS

Endless Legs Code	Eye & Eye Legs Code	Leg Color	Vertical Capacity in lbs.	Minimum Leg Length B to B
ENR1	EER1	PURPLE	2080	4'
ENR2	EER2	GREEN	4240	4'
ENR3	EER3	YELLOW	6720	4'
ENR4	EER4	TAN	8480	4'
ENR5	EER5	RED	10560	4'
ENR6	EER6	WHITE	13440	8'
ENR7	EER7	BLUE	16960	8'

DOUBLE LEG ROUNDUP BRIDLE SLINGS


Endless Legs Code	Eye & Eye Legs Code	Leg Color	*Capacity in lbs. at Horizontal Angle			Minimum Leg Length B to B
			60 Degree	45 Degree	30 Degree	
ENR1	EER1	PURPLE	3600	2960	2080	4'
ENR2	EER2	GREEN	7360	6000	4240	4'
ENR3	EER3	YELLOW	11600	9440	6720	4'
ENR4	EER4	TAN	14640	11920	8480	4'
ENR5	EER5	RED	18240	14880	10560	4'
ENR6	EER6	WHITE	23200	18960	13440	8'
ENR7	EER7	BLUE	29360	23920	16960	8'

QUAD (4) LEG ROUNDUP BRIDLE

Endless Legs Code	Eye & Eye Legs Code	Leg Color	*Capacity in lbs. at Horizontal Angle			Minimum Leg Length B to B
			60 Degree	45 Degree	30 Degree	
ENR1	EER1	PURPLE	7200	5888	4160	4'
ENR2	EER2	GREEN	14720	12000	8480	4'
ENR3	EER3	YELLOW	23200	18880	13440	4'
ENR4	EER4	TAN	29280	23840	16960	4'

*Before ordering slings that are going to be used in a chemically active environment, contact Liftex® Customer Service, to recommend the right sling for the right usage.

Chemically Active Environments can affect the strength of webbing slings in varying degrees, ranging from little to total degradation.



WARNING

SLING FAILURE CAN CAUSE
DEATH OR INJURY
SLING FAILURE RESULTS FROM
MISUSE, DAMAGE, AND
EXCESSIVE WEAR

ADHERE TO INDUSTRY
STANDARDS & REGULATIONS