




www.liftex.com  
(800) 299-0900

### ENDLESS ROUND SLING CAPACITY CHART

	Part Number	Vertical	Choker	Basket	Minimum Length	Approx. Diameter	Approx. WT / FT
<b>PURPLE</b>	ENR1	2600	2100	5200	3'	.625"	0.3 LB
<b>GREEN</b>	ENR2	5300	4200	10600	3'	.875"	0.4 LB
<b>YELLOW</b>	ENR3	8400	6700	16800	3'	1.125"	0.5 LB
<b>TAN</b>	ENR4	10600	8500	21200	3'	1.125"	0.6 LB
<b>RED</b>	ENR5	13200	10600	26400	3'	1.375"	0.8 LB
<b>WHITE</b>	ENR6	16800	13400	33600	6'	1.375"	0.9 LB
<b>BLUE</b>	ENR7	21200	17000	42400	6'	1.625"	1.3 LB
<b>ORANGE</b>	ENR8	25000	20000	50000	6'	1.750"	1.6 LB
<b>ORANGE</b>	ENR9	31000	24800	62000	6'	2.125"	2.0 LB
<b>ORANGE</b>	ENR10	40000	32000	80000	6'	2.350"	2.6 LB
<b>ORANGE</b>	ENR11	53000	42400	106000	8'	3.150"	3.4 LB
<b>ORANGE</b>	ENR12	66000	52800	132000	8'	3.950"	4.3 LB
<b>ORANGE</b>	ENR13	90000	72000	180000	8'	4.800"	5.9 LB

\*Before ordering slings that are going to be used in a chemically active environment, contact Liftex® Customer Service, to recommend the right sling for the right usage.

Chemically Active Environments can affect the strength of webbing slings in varying degrees, ranging from little to total degradation.



**WARNING**

SLING FAILURE CAN CAUSE  
**DEATH OR INJURY**  
SLING FAILURE RESULTS FROM MISUSE, DAMAGE, AND EXCESSIVE WEAR

---

ADHERE TO INDUSTRY STANDARDS & REGULATIONS