

### NEW & EXCLUSIVE FROM LIFTEX®!

SUPERTECHLON® Round Slings offer an enhanced combination of strength and flexibility with patented abrasion resistant outer jacket.

#### Features and Benefits

All the benefits of a Liftex polyester round sling plus:

- Patented abrasion resistant techlon™ outer cover delivers up to twice the durability of a standard cover
- Stripe coded to assist in identifying sling capacity (each stripe equals 3000 lbs of vertical capacity) — rated higher than Industry standard
- Visible print coded with vertical lifting capacity printed on the outer cover
- Color coded for ease of identification
- All in one fly tags and identification tag for ease of use
- Individually serialized for traceability



#### Capacity Chart & Specifications

All capacities listed below meet or exceed all applicable US industry standards having a 5:1 design factor

Code	Color	Rated Capacity (lbs.)			Minimum Length (ft.)	Relaxed Body Diameter (in.)	Sleeve Width (in.)	Approximate Weight (lbs/ft)
		Vertical <sup>1</sup>	Choker <sup>2</sup>	Basket <sup>3</sup>				
ST-ENR-3000	PURPLE	3,000	2,400	6,000	3'	0.63"	1.50"	0.3
ST-ENR-6000	GREEN	6,000	4,800	12,000	3'	0.88"	1.75"	0.4
ST-ENR-9000	YELLOW	9,000	7,200	18,000	3'	1.13"	2.13"	0.6
ST-ENR-12000	TAN	12,000	9,600	24,000	3'	1.25"	2.13"	0.7
ST-ENR-15000	RED	15,000	12,000	30,000	3'	1.56"	2.69"	0.9
ST-ENR-18000	WHITE	18,000	14,400	36,000	3'	1.63"	2.88"	1.0
ST-ENR-24000	BLUE	24,000	19,200	48,000	4'	2.00"	3.50"	1.7
ST-ENR-30000	ORANGE	30,000	24,000	60,000	4'	2.56"	4.72"	2.0

Slings manufactured by Liftex. Slings are made to order up to 40ft in length.

**HOW TO ORDER INSTRUCTIONS = CODE - LENGTH - D**



**WARNING**

**SLING FAILURE CAN CAUSE DEATH OR INJURY RESULTING FROM MISUSE, DAMAGE, AND EXCESSIVE WEAR. ADHERE TO INDUSTRY STANDARDS AND REGULATIONS.**



Stripe Coding

