



the world's best slings

www.liftex.com


(800) 299-0900

REVERSED EYE CAPACITY CHART

		Rated Capacity (lbs.)			Eye Dimensions		
Part Number	Sling Width (inches)	Vertical	Choker	Vertical Basket	Width (inches)	Length (inches)	Min. Standard Length (ft)
RE192	2	4600	3680	9200	1	9	3
RE292	2	7700	6160	15400	1	12	3
RE193	3	6900	5520	13800	1-1/2	12	4
RE293	3	11600	9280	23200	1-1/2	12	4
RE194	4	8600	6880	17200	1	12	4
RE294	4	14500	11600	29000	2	18	6
RE394	4	20400	16320	40800	2	18	6
RE494	4	23000	18400	46000	2	18	6
RE196	6	12000	9600	24000	1-1/2	14	6
RE296	6	17400	13920	34800	1-1/2	18	6
RE396	6	26500	21200	53000	3	20	6
RE496	6	34000	27200	68000	3	24	6

**Before ordering slings that are going to be used in a chemically active environment, contact Liftex® Customer Service, to recommend the right sling for the right usage.*

Chemically Active Environments can affect the strength of webbing slings in varying degrees, ranging from little to total degradation.



WARNING

SLING FAILURE CAN CAUSE
DEATH OR INJURY

SLING FAILURE RESULTS FROM MISUSE, DAMAGE, AND EXCESSIVE WEAR

ADHERE TO INDUSTRY STANDARDS & REGULATIONS