




www.liftex.com
 (800) 299-0900

POLYESTER MARINE SLINGS

| Sling Width | Part Number | Basket Capacity | Loose Pin Hardware | Fabric Eye Disconnect |
|-------------|-------------|-----------------|--------------------|-----------------------|
| 6" | MS196P | 18600 | LPF6 | N/A |
| 8" | MS198P | 24800 | LPF6 | 3&2 |
| 8" | MS298P | 44000 | N/A | 3&2 |
| 10" | MS19510P | 31000 | LPF5 | 3&2 |
| 10" | MS29510P | 55000 | N/A | 3&2 |
| 12" | MS19612P | 37200 | LPF6HD | 3&2 |
| 12" | MS29612P | 66000 | N/A | 3&2 |
| 16" | MS19816P | 44000 | N/A | 4&3 |
| 16" | MS29816P | 88000 | N/A | 4&3 |

**Before ordering slings that are going to be used in a chemically active environment, contact Liftex® Customer Service, to recommend the right sling for the right usage.*

Chemically Active Environments can affect the strength of webbing slings in varying degrees, ranging from little to total degradation.



WARNING

SLING FAILURE CAN CAUSE
DEATH OR INJURY
 SLING FAILURE RESULTS FROM MISUSE, DAMAGE, AND EXCESSIVE WEAR

ADHERE TO INDUSTRY STANDARDS & REGULATIONS