




www.liftex.com  
(800) 299-0900

### CHOKER HARDWARE CAPACITY CHART

Part Number	Sling Width (inches)	Rated Capacity (lbs.)			Min. Standard Length (ft)
		Vertical	Choker	Vertical Basket	
CHS1-92	2	3,200	2,560	6,400	3
CHS2-92	2	6,400	5,120	12,800	3
CHS3-92	2	8,300	6,640	16,600	3
CHS4-92	2	12,400	9,920	24,800	3
CHS1-93	3	4,800	3,840	9,600	3
CHS2-93	3	8,900	7,120	17,800	3
CHS3-93	3	12,500	10,000	25,000	3
CHS4-93	3	17,000	13,600	34,000	3
CHS1-94	4	6,400	5,120	12,800	3
CHS2-94	4	11,500	9,200	23,000	3
CHS3-94	4	16,000	12,800	32,000	3
CHS4-94	4	22,000	17,600	44,000	3
CHS1-96	6	9,600	7,680	19,200	3
CHS2-96	6	16,500	13,200	33,000	3
CHS3-96	6	23,000	18,400	46,000	3
CHS4-96	6	33,000	26,400	66,000	3
CHS1-98	8	12,800	10,240	25,600	6
CHS2-98	8	22,400	17,920	44,800	6
CHS3-98	8	30,700	24,560	61,400	6
CHS4-98	8	44,000	35,200	88,000	6
CHS1-910	10	16,000	12,800	32,000	6
CHS2-910	10	28,000	22,400	56,000	6
CHS3-910	10	36,800	29,440	73,600	6
CHS4-910	10	55,000	44,000	110,000	6
CHS1-912	12	19,200	15,360	38,400	6
CHS2-912	12	32,000	25,600	64,000	6
CHS3-912	12	44,000	35,200	88,000	6
CHS4-912	12	66,000	52,800	132,000	6

*\*Before ordering slings that are going to be used in a chemically active environment, contact Liftex® Customer Service, to recommend the right sling for the right usage.*

*Chemically Active Environments can affect the strength of webbing slings in varying degrees, ranging from little to total degradation.*



**WARNING**

SLING FAILURE CAN CAUSE  
**DEATH OR INJURY**  
SLING FAILURE RESULTS FROM  
MISUSE, DAMAGE, AND  
EXCESSIVE WEAR

---

ADHERE TO INDUSTRY  
STANDARDS & REGULATIONS