



www.liftex.com
 (800) 299-0900


CAPACITY CHART FOR CHAIN SLINGS

G100 CHAIN SIZE	SINGLE LEG	DOUBLE LEG			TRIPLE & QUAD LEG		
		90°	60°	45°	30°	60°	45°
9/32	4300	7400	6100	4300	11200	9100	6400
5/16	5700	9900	8100	5700	14800	12100	8500
3/8	8800	15200	12400	8800	22900	18700	13200
1/2	15000	26000	21200	15000	39000	31800	22500
5/8	22600	39100	32000	22600	58700	47900	33900
3/4	35300	61100	49900	35300	91700	74900	53000
7/8	42700	74000	60400	42700	110900	90600	64000

Working load limits are valid between temperatures of -40°F and 400°F

**Before ordering slings that are going to be used in a chemically active environment, contact Liftex® Customer Service, to recommend the right sling for the right usage.*

Chemically Active Environments can affect the strength of webbing slings in varying degrees, ranging from little to total degradation.



WARNING

SLING FAILURE CAN CAUSE
DEATH OR INJURY
 SLING FAILURE RESULTS FROM
 MISUSE, DAMAGE, AND
 EXCESSIVE WEAR

ADHERE TO INDUSTRY
 STANDARDS & REGULATIONS