



the world's best slings

www.liftex.com

(800) 299-0900


### BASKET HARDWARE CAPACITY CHART

Part Number	Sling Width (inches)	Rated Capacity (lbs.)		Min. Standard Length (ft)
		Vertical	Vertical Basket	
BHS1-92	2	3,200	6,400	3
BHS2-92	2	6,400	12,800	3
BHS3-92	2	8,300	16,600	3
BHS4-92	2	10,000	20,000	3
BHS1-93	3	4,800	9,600	3
BHS2-93	3	8,900	17,800	3
BHS3-93	3	12,500	25,000	3
BHS4-93	3	14,900	29,800	3
BHS1-94	4	6,400	12,800	3
BHS2-94	4	11,500	23,000	3
BHS3-94	4	16,000	32,000	3
BHS4-94	4	19,800	39,600	3
BHS1-96	6	9,600	19,200	3
BHS2-96	6	16,500	33,000	3
BHS3-96	6	23,000	46,000	3
BHS4-96	6	29,800	59,600	3
BHS1-98	8	12,800	25,600	6
BHS2-98	8	22,400	44,800	6
BHS3-98	8	30,700	61,400	6
BHS4-98	8	39,700	79,400	6
BHS1-910	10	16,000	32,000	6
BHS2-910	10	28,000	56,000	6
BHS3-910	10	36,800	73,600	6
BHS4-910	10	49,600	99,200	6
BHS1-912	12	19,200	38,400	6
BHS2-912	12	32,000	64,000	6
BHS3-912	12	44,000	88,000	6
BHS4-912	12	59,500	119,000	6

Aluminum Hardware Slings- Rated Capacity					
Part Number	Sling Width (inches)	Vertical	Choker	Vertical Basket	Min. Standard Length
BHA1-92	2	3,200	2,560	6,400	3
BHA1-93	3	4,800	3,840	9,600	3
BHA1-94	4	6,400	5,120	12,800	3
BHA1-96	6	9,600	7,680	19,200	3
CHA1-92	2	3,200	2,560	6,400	3
CHA1-93	3	4,800	3,840	9,600	3
CHA1-94	4	6,400	5,120	12,800	3
CHA1-96	6	9,600	7,680	19,200	3

*\*Before ordering slings that are going to be used in a chemically active environment, contact Liftex® Customer Service, to recommend the right sling for the right usage.*

*Chemically Active Environments can affect the strength of webbing slings in varying degrees, ranging from little to total degradation.*



**WARNING**

SLING FAILURE CAN CAUSE  
**DEATH OR INJURY**  
SLING FAILURE RESULTS FROM MISUSE, DAMAGE, AND EXCESSIVE WEAR

---

ADHERE TO INDUSTRY STANDARDS & REGULATIONS