



www.liftex.com  
(800) 299-0900

### SINGLE LEG SLINGS

Part Number	Top Fitting	*Capacity in lbs. at Horizontal Angle	
		Bottom Fitting	90°
SOS-EE191	Oblong Master Link	Sling Eye Hook	1600
SOO-EE191	Oblong Master Link	Oblong Master Link	1600
SSS-EE191	Sling Eye Hook	Sling Eye Hook	1600
SOS-EE291	Oblong Master Link	Sling Eye Hook	3200
SOO-EE291	Oblong Master Link	Oblong Master Link	3200
SSS-EE291	Sling Eye Hook	Sling Eye Hook	3200
SOS-EE292	Oblong Master Link	Sling Eye Hook	6400
SOO-EE292	Oblong Master Link	Oblong Master Link	6400
SSS-EE292	Sling Eye Hook	Sling Eye Hook	6400

### DOUBLE LEG SLINGS


Part Number	Top Fitting	Bottom Fitting	*Capacity in lbs. at Horizontal Angle		
			60°	45°	30°
DOS-EE191	Oblong Master Link	Sling Eye Hook	2770	2260	1600
DOO-EE191	Oblong Master Link	Oblong Master Link	2770	2260	1600
DOS-EE291	Oblong Master Link	Sling Eye Hook	5540	4520	3200
DOO-EE291	Oblong Master Link	Oblong Master Link	5540	4520	3200
DOS-EE292	Oblong Master Link	Sling Eye Hook	11090	9050	6400
DOO-EE292	Oblong Master Link	Oblong Master Link	11090	9050	6400

### QUADRUPLE LEG SLINGS

Part Number	Top Fitting	Bottom Fitting	*Capacity in lbs. at Horizontal Angle		
			60°	45°	30°
QOS-EE191	Oblong Master Link	Sling Eye Hook	5540	4520	3200
QOO-EE191	Oblong Master Link	Oblong Master Link	5540	4520	3200
QOS-EE291	Oblong Master Link	Sling Eye Hook	11090	9050	6400
QOO-EE291	Oblong Master Link	Oblong Master Link	11090	9050	6400
QOS-EE292	Oblong Master Link	Sling Eye Hook	22180	18100	12800
QOO-EE292	Oblong Master Link	Oblong Master Link	22180	18100	12800

*\*Before ordering slings that are going to be used in a chemically active environment, contact Liftex® Customer Service, to recommend the right sling for the right usage.*

*Chemically Active Environments can affect the strength of webbing slings in varying degrees, ranging from little to total degradation.*



**WARNING**

SLING FAILURE CAN CAUSE  
**DEATH OR INJURY**  
SLING FAILURE RESULTS FROM  
MISUSE, DAMAGE, AND  
EXCESSIVE WEAR

---

ADHERE TO INDUSTRY  
STANDARDS & REGULATIONS