



SLING PROTECTION

featuring

Dyneema® Cordura®









EXTREEMA® Sling Protection Products

It is often misunderstood that the outer sleeve (jacket) of a roundsling is meant to protect the core load bearing fibers from damage. The outer sleeve (jacket) functions mostly to contain and organize the core load bearing fibers. *International standards and norms require that slings be protected from potential damage*. Extreema® sling protection products are useful in fulfilling these international standards and norms.

From ASME B30.9-1.10.4(d)/B30.9-5.10.4(d)/B30.9-6.10.4(d)/B30.9-7.10.4(d), slings in contact with edges, corners, protrusions, or abrasive surfaces shall be protected with a material of sufficient strength, thickness and construction to prevent damage.

From EN 1492, regulations for safe roundsling use, the sling should be protected on the anchoring point (shackles, pins, etc.) as well as the lifting appliance (crane hook).

From C.6 and D.3.7 of EN 1492-2:2000+A1:2008, slings should be protected from edges, friction and abrasion, whether from the load or the lifting appliance. Where protection against damage from edges and/or abrasion is supplied as part of the sling, this should be correctly positioned. It may be necessary to supplement this with addition protection.

TEST LIFTS SHOULD ALWAYS BE PERFORMED TO DETERMINE THAT SLING PROTECTION PRODUCTS UTILIZED ARE SUFFICIENT TO PROTECT SLING FROM DAMAGE.








EXTREEMA® Sling Protection Products





















EXTREEMA® DYNEEMA® SLING PROTECTION

Polyester Roundsling			
Color	Single Leg Double Le		
ENR1	EP-L1	EP-L2	
ENR2	EP-L1	EP-L3	
ENR3	EP-L1	EP-L3	
ENR4	EP-L3	EP-L4	
ENR5	EP-L4	EP-L5	
ENR6	EP-L4	EP-L5	
ENR7	EP-L4	EP-L5	
ENR8	EP-L5	EP-L6	
ENR9	EL-L5	EP-L7	
ENR10	EP-L6	EP-L8	
ENR11	EP-L7	EP-L9	
ENR12	EP-L7	EP-L10	
ENR13	ON REQUEST	ON REQUEST	
ENR14	ON REQUEST	ON REQUEST	

Extreema® Roundsling			
WLL (T)	Single Leg		
1-5T	EP-L1	EP-L2	
6-10T	EP-L2	EP-L3	
12	EP-L3	EP-L4	
15	EP-L3	EP-L4	
20	EP-L5	EP-L6	
25	EP-L5	EP-L6	
30	EP-L5	EP-L6	
35	EP-L5	EP-L6	
40	EP-L5	EP-L6	
45	EP-L5	EP-L6	
50	EP-L6	EP-L7	
60	EP-L6	EP-L7	
70	EP-L6	EP-L7	
80	EP-L7	EP-L8	
90	EP-L7	EP-L8	
100	EP-L8 EP-L9		
>100	ON REQUEST	ON REQUEST	

Web Sling			
Width	Single Leg		
1"	EP-L1		
2"	EP-L2		
3"	EP-L4		
4"	EP-L6		
6"	EP-L7		
8"	EP-L11		
10"	EP-L12		
12"	EP-L13		

EP-L Extreema® sling protection products are manufactured from 100% Dyneema®. Dyneema is well known for its high cut resistance.







EXTREEMA® CORDURA® SLING PROTECTION

Polyester Roundsling			
Color	Single Leg Double Le		
ENR1	EP-C1	EP-C2	
ENR2	EP-C1	EP-C2	
ENR3	EP-C1	EP-C3	
ENR4	EP-C3	EP-C4	
ENR5	EP-C4	EP-C5	
ENR6	EP-C4	EP-C5	
ENR7	EP-C4	EP-C5	
ENR8	EP-C5	EP-C6	
ENR9	EP-C5	EP-C7	
ENR10	EP-C6	EP-C8	
ENR11	EP-C7	EP-C9	
ENR12	EP-C7	EP-C10	
ENR13	ON REQUEST	ON REQUEST	
ENR14	ON REQUEST	ON REQUEST	

Extreema® Roundsling			
WLL (T)	Single Leg	Double Leg	
1-5T	EP-C1	EP-C2	
6-10T	EP-C2	EP-C3	
12	EP-C3	EP-C4	
15	EP-C3	EP-C4	
20	EP-C4	EP-C6	
25	EP-C5	EP-C6	
30	EP-C5	EP-C6	
35	EP-C5	EP-C6	
40	EP-C5	EP-C6	
45	EP-C5	EP-C6	
50	EP-C6	EP-C7	
60	EP-C6	EP-C7	
70	EP-C6	EP-C7	
80	EP-C7	EP-C8	
90	EP-C7	EP-C8	
100	EP-C8	EP-C9	
>100	ON REQUEST	ON REQUEST	

Web Sling			
Width	Single Leg		
1"	EP-C1		
2"	EP-C2		
3"	EP-C4		
4"	EP-C6		
6"	EP-C7		
8"	EP-C11		
10"	EP-C12		
12"	EP-C13		

EP-C Extreema® sling protection products are manufactured from 100% Cordura®. Cordura is well known for its high abrasion and heat resistance providing excellent protection on smooth surfaces.







EXTREEMA® DYNEEMA® TUBULAR SLING PROTECTION

Part #	Width (IN) (APPROX)	Fits Width of Webbing (2-ply)	Polyester Roundsling (2-Legs)	Extreema® Roundsling (2-legs)
EP-XL80	3	1-2	ENR1-ENR2	1T>8T
EP-XL110	4	3	ENR3-ENR4	10T>12T
EP-XL130	5	4	ENR5-ENR6	15T>20T
EP-XL160	6		ENR7	25T>40T
EP-XL190	7	6	ENR8-ENR9	45T>T55
EP-XL230	9		ENR10-ENR12	60T>70T
EP-XL260	10	10		75T>80T
EP-XL290	11		ENR13	85T>95T
EP-XL310	12	12		100T>110T



Part#	Width (IN) (APPROX)	Fits Width of Webbing (2-ply)	Polyester Roundsling (2-Legs)	Extreema® Roundsling (2-legs)
EP-XXL85	3	1-2	ENR1-ENR2	1T>8T
EP-XXL115	4	3	ENR3-ENR4	10T>12T
EP-XXL130	5	4	ENR5-ENR6	15T>20T
EP-XXL160	6		ENR7	25T>40T
EP-XXL190	7	6	ENR8-ENR9	45T>T55
EP-XXL230	9		ENR10-ENR12	60T>70T
EP-XXL260	10	10		75T>80T
EP-XXL290	11		ENR13	85T>95T





EXTREEMA® Sling Protection Products













Contact Us



Liftex Corportion

780 Falcon Circle #105 Warminster PA 18974 1-800-290-2900 1-215-957-0810 1-215-957-9180 (fax) www.liftex.com

HOUSTON | CHICAGO GREENVILLE | SEATTLE PHILADELPHIA

Liftex Mexico

Av Tezozomoc 94 San Miguel Amantla 02700 Ciudad de Mexico CDMX Mexico



